RESEARCHING ENERGY-SAVING TECHNOLOGIES AND EFFICIENCY OPTIMIZATION IN BATTERY SYSTEMS OF NEW ENERGY VEHICLES

Steffen Kersten, professor
Technische Universität Dresden, Germany.
Oybek Daminov, Associate Professor
Akbar Juraboev, PhD researcher, Kamol Erkinov, Master Student
at Tashkent state technical University named after Islam Karimov

Introduction

As the global automotive industry aggressively scales up the production of New Energy Vehicles (NEVs), including Battery Electric Vehicles (BEVs) and Hybrid Electric Vehicles (HEVs), engineers face a persistent challenge: "range anxiety." Historically, the immediate solution to extending driving range was simply to increase the physical size and capacity of the Lithium-ion battery packs. However, this brute-force approach is highly unsustainable. Larger batteries add massive weight to the vehicle, increase manufacturing costs, and consume vast amounts of critical raw materials. Consequently, the industry has reached a tipping point where adding battery cells yields diminishing returns. This research argues that the future of NEV development lies not in bigger batteries, but in extreme energy efficiency. By aggressively minimizing parasitic losses across internal subsystems, automakers can drastically extend vehicle range while utilizing lighter, more affordable battery packs.

There are main two different types of management battery systems. And some literatures was written about colling types of them: general types of colling battery packs is active colling, and passive colling.

Active vs. Passive Battery Management Systems

The first critical area of intervention is the Battery Management System (BMS). Inside a high-voltage battery pack, individual cells naturally develop slight voltage imbalances over time. Traditional passive BMS architectures solve this by simply draining power from the strongest cells through resistors, literally burning away valuable stored energy as waste heat until all cells match the weakest one.

Modern engineering is replacing this inefficient method with AI-governed Active BMS. Active systems utilize bi-directional DC-DC converters to intelligently shuttle electrical charge from high-capacity cells directly into weaker cells. This dynamic redistribution not only prevents energy from being wasted as Joule heating but also ensures that the entire capacity of the battery pack is fully utilized, extending the practical driving range per charge.

Holistic Thermal Management in Extreme Climates

The second major source of parasitic loss is thermal regulation, particularly in harsh climates. Extreme cold severely degrades battery performance, and traditional NEVs rely on power-hungry Positive Temperature Coefficient (PTC)

heaters to warm the cabin and the battery. These resistive heaters can consume up to 20% of the vehicle's total range.

To overcome this, advanced holistic Battery Thermal Management Systems (BTMS) are being deployed. Instead of generating heat from electricity, these systems utilize integrated heat pumps that scavenge ambient heat—even in cold weather—and recover waste heat generated by the electric motors and power inverters. Furthermore, the integration of Phase Change Materials (PCM) around the battery modules provides passive thermal absorption, shielding the cells from sudden temperature spikes without drawing any electrical power.

Optimizing Kinetic Recovery

Finally, maximizing energy efficiency requires advanced kinetic recovery through regenerative braking. Rather than applying a standard deceleration force, modern predictive algorithms, enhanced by techniques like Particle Swarm Optimization (PSO), analyze driving cycles, vehicle mass, and road gradients in real-time. This allows the vehicle to capture the maximum possible kinetic energy and convert it back into electrical storage without compromising passenger comfort.

The optimization of energy usage within New Energy Vehicles has evolved far beyond the simple installation of larger battery packs. This research confirms that implementing advanced energy-saving technologies is highly effective. By transitioning to AI-governed active battery management, integrating waste-heat recovery thermal systems, and maximizing kinetic energy recovery through algorithmically optimized regenerative braking, automakers can profoundly reduce parasitic power losses. These advancements not only maximize the effective range of NEVs but also drastically extend the lifecycle of the battery cells, ensuring a more sustainable future for global transportation.

By combining active cell balancing, waste-heat scavenging heat pumps, and AI-optimized energy recovery, automakers can profoundly reduce power waste. These intelligent interventions not only stretch the effective range of NEVs but significantly slow down chemical degradation, ensuring a longer, more sustainable lifespan for the battery cells

References

1. Wei, Y., Li, K., & Liu, Z. (2024). "Modeling and control strategy optimization of battery pack thermal management system considering aging." Applied Thermal Engineering, 256, 124153. https://doi.org/10.1016/j.applthermaleng.2024.124153

2. Aghili, S.A.; Haji Mohammad Rezaei, A.;Tafazzoli,M.; Khanzadi,M.;Rahbar,M .Artificial Intelligence Approaches to Energy ManagementinHVACSystems: A Systematic Review. Buildings 2025, 15, 1008. https://doi.org/10.3390/buildings15071008

3. EUROBAT Association of European Automotive and Industrial Battery Manufacturers Date of publication : June 2024, https://www.eurobat.org/wp-content/uploads/2024/11/white-paper-innovation-roadmap-2024-Tech-Annex_web_version-3.pdf