RESEARCHING METHODS TO REDUCE OR ELIMINATE EXHAUST EMISSIONS FROM AUTOMOTIVE INTERNAL COMBUSTION ENGINES

Oybek Daminov, Associate Professor
Tashkent State Technical University, Uzbekistan
Jamoliddin Turdiev, Senior Teacher
Tashkent State Technical University, Uzbekistan
Diyorbek Marufjonov, Master's Student
Tashkent State Technical University, Uzbekistan

Introduction

For over a century, the internal combustion engine (ICE) has served as the undisputed beating heart of global transportation. Entire economies, urban landscapes, and industrial networks have been constructed around its reliable hum. Today, however, that vast mechanical legacy is colliding directly with a profound environmental crisis. The global automotive industry currently finds itself forced to navigate what is arguably the most daunting and complex transition in its entire history, driven almost entirely by the urgent and non-negotiable shift toward net-zero climate targets.

As international regulatory bodies clamp down on pollution – most notably through the enforcement of increasingly stringent and uncompromising emission limits such as the upcoming Euro 7 standards – it has become painstakingly clear that the traditional reliance on fossil fuels is rapidly becoming obsolete. Yet, when we look at the sheer scale of the automotive world, a massive logistical and economic dilemma immediately arises. The existing industrial ecosystem is practically unfathomable in its size. There is a deeply rooted, century-old infrastructure in place, encompassing everything from global manufacturing supply chains to highly specialized engineering expertise specifically built around the internal combustion engine. To simply discard all of this hard-earned mechanical infrastructure in favour of entirely new propulsion systems is not just incredibly disruptive; it is economically impractical on a global scale. Because of this, researchers and engineers are realizing that finding a reliable transitional – and ultimately permanent – solution to clean up how internal combustion engines operate is far more than just a fleeting environmental necessity.

It has become a vital, cornerstone economic strategy to save millions of jobs and salvage trillions of dollars in existing manufacturing capabilities. This specific body of research explores the highly compelling viability of keeping the core, proven architecture of internal combustion engines largely intact, while fundamentally and radically changing exactly what it is that they burn. The focus of this transition relies heavily on the utilization of alternative, completely carbon-free fuels, with a specific emphasis on anhydrous ammonia and hydrogen blends.

The Challenge of Carbon-Free Fuels

When scientists and engineers sit down to meticulously evaluate zero-carbon fuel alternatives to replace gasoline and diesel, ammonia quickly emerges from

the pack as a highly promising and attractive candidate. Unlike many experimental synthetic fuels, ammonia already benefits from a massive, well-established global supply chain thanks to its widespread use in the agricultural sector. Furthermore, it boasts a relatively high energy density, and when compared to the extreme cryogenic freezing requirements of pure liquid hydrogen, ammonia is significantly easier to transport and store at scale. However, taking that ammonia and utilizing it in its pure form inside the violent, fast-paced environment of a combustion chamber presents incredibly severe engineering hurdles.

As an automotive fuel, ammonia is notoriously stubborn and difficult to ignite. It demands an exceptionally high amount of ignition energy just to start the combustion process. Even if you manage to ignite it successfully, it suffers from a very slow laminar flame speed, meaning the fire simply does not propagate across the cylinder fast enough to keep up with the rapid movements of a modern engine piston. Because of these sluggish chemical properties, the engine fundamentally struggles to maintain stable, predictable combustion under varying loads and throttle inputs. This instability creates a massive risk scenario for tailpipe emissions. If the engine misfires or fails to burn the ammonia completely during the power stroke, it risks emitting highly toxic unburned ammonia slip directly into the atmosphere.

Additionally, poor combustion characteristics can lead to the generation of extraordinarily high levels of nitrogen oxides (NOx). If these harmful pollutants are allowed to escape the tailpipe, the entire environmental purpose of switching away from fossil fuels is completely defeated.

Technological Interventions: Hydrogen Reforming and TJI

To actively resolve these inherent, deeply frustrating combustion instabilities, our research closely highlights and examines a sophisticated dual-fuel methodology that integrates on-board hydrogen generation directly into the vehicle's fuel system. The concept works by utilizing an advanced on-board catalytic reformer. Before the fuel ever reaches the engine, a small, precisely measured portion of the liquid ammonia is chemically cracked inside this reformer to release raw hydrogen gas. This dynamically introduced hydrogen serves a critical purpose: it acts as a remarkably powerful combustion promoter. While ammonia is slow and lazy, hydrogen has an extremely fast flame speed and incredibly wide flammability limits.

By strategically blending this highly reactive hydrogen back together with the base ammonia right before ignition, engineers can drastically improve the overall reactivity of the air-fuel mixture within the cylinder. Yet, even with this potent new fuel blend, simply injecting it directly into a standard, old-fashioned engine cylinder is still insufficient to meet the ultra-strict efficiency targets demanded by modern legislation. The real, paradigm-shifting breakthrough lies in combining this unique hydrogen-ammonia fuel blend with an active pre-chamber turbulent jet ignition (TJI) system. The architecture of a TJI setup is a marvel of modern combustion engineering.

Instead of sitting out in the open main cylinder, the spark plug is safely isolated inside a tiny, separate pre-chamber. During the intake process, a highly concentrated, rich pocket of the hydrogen-ammonia mix is directed specifically into this small pre-chamber and ignited. Because the space is so confined and the mixture is so reactive, the resulting combustion is incredibly intense. The extreme pressure forces high-velocity, super-heated jets of flame to shoot out through tiny, precisely machined nozzles directly into the much larger main cylinder. These fiery jets act like a shotgun blast of ignition points, causing the larger, lean ammonia mixture waiting in the main cylinder to ignite rapidly, thoroughly, and completely uniformly.

Engine Control and Future Outlook

The real-world results of combining these complex systems are nothing short of extraordinary. Extensive empirical data gathered during testing heavily demonstrates that this hydrogen-assisted TJI methodology drastically improves the overall thermal efficiency of the engine block. In fact, when tuned correctly, this system is capable of effectively matching, or in some specific operational ranges even exceeding, the highly praised thermodynamic performance typically associated with heavy-duty diesel powertrains. Of course, to successfully manage a combustion process this volatile and complex, traditional mechanical engine systems are no longer viable.

Advanced electronic control units (ECUs) boasting massive processing power must be deployed to strictly govern the ultra-high-pressure injection timing. These modern ECUs are constantly calculating real-time sensor data from across the engine block. Their primary objective during this process is to strictly prevent the formation of localized, fuel-rich zones within the combustion chamber, as these dense pockets of unburned fuel are the primary chemical culprits responsible for the unwanted formation of NOx emissions. When we step back and look at the trajectory of this research, a very clear and optimistic picture begins to form regarding the future of transportation.

The complete and total elimination of harmful exhaust emissions from automotive internal combustion engines is not just a distant theoretical dream; it is scientifically and technologically feasible today. While we are currently relying heavily on advanced, expensive exhaust after-treatment systems to temporarily minimize the pollutants generated from legacy fossil fuels, the definitive, permanent long-term solution clearly lies in the widespread, global adoption of zero-carbon fuels.

Ammonia and hydrogen stand at the very forefront of this revolution. Particularly when they are cleverly utilized in tandem with cutting-edge advanced turbulent jet ignition systems and active pre-chamber technology, they represent a monumental engineering breakthrough. These combined technologies provide a vital bridge to the future. They ensure that the massive global automotive sector can successfully achieve its strict environmental mandates and climate goals without being forced into discarding the vast, brilliantly established engineering foundation of the internal combustion engine.

Ultimately, this delicate synthesis of combining zero-carbon alternative fuels with highly advanced, computer-controlled ignition and management systems proves beyond a shadow of a doubt that absolute zero-emission engine operation is a tangible reality today. By bravely adopting and refining these specific technologies, the automotive sector can definitively secure its place in a green future, honouring its environmental obligations while simultaneously preserving the established mechanical foundation that built the modern world.

References

1. Huynh, D. N. L., Nguyen, T. H., Nguyen, D. C., Vo, A. V., Nguyen, D. T., Nguyen, V. Q., & Le, H. C. (2024). "Using hydrogen as potential fuel for internal combustion engines: A comprehensive assessment." International Journal of Renewable Energy Development, 14(1), 83-103. https://ijred.cbiore.id/index.php/ijred/article/view/60707/0

2. Maximilian Held, Yannic Tönges, Dominik Pélerin, Martin Härtl, Georg Wachtmeister and Jakob Burger. Correction: On the energetic efficiency of producing polyoxymethylene dimethyl ethers from CO2 using electrical energy. Energy Environ. Sci., 2019, 12, 2591-2592. https://pubs.rsc.org/en/content/articlehtml/2019/ee/c9ee90035g

3. Zhang, H., Lei, N., & Wang, Z. (2024). "Ammonia-hydrogen propulsion system for carbon-free heavy-duty vehicles." Applied Energy, 369, 123505. https://doi.org/10.1016/j.apenergy.2024.123505

4. Musabekov Z., Mirzaabdullaev J., Daminov O., Kurbanov A. Identification, practical, theoretical and analytical results of exhaust gases in vehicle internal combustion engines. 4th International Conference on Research of Agricultural and Food Technologies (I-CRAFT). 2024 September 11 & 13 Tashkent, Uzbekistan. ISBN: 978-625-99572-2-7, 90-94 pp.

5. Reggeti, S. A., & Northrop, W. F. (2024). "Lean ammonia-fueled engine operation enabled by hydrogen-assisted turbulent jet ignition." Frontiers in Mechanical Engineering, 10, 1368717. https://doi.org/10.3389/fmech.2024.1368717

6. Valera-Medina, A., Xiao, H., Owen-Jones, M., David, W. I. F., & Bowen, P. J. (2018). "Ammonia for power." Progress in Energy and Combustion Science, 69, 63-102. https://doi.org/10.1016/j.pecs.2018.07.001